









0/1-10V Dimmer Panel


| Model Name | Product Name | Pictrue | Parameters | Key Feature | Recommended Products | Distinguish Between Similar Products |
|------------|---|--|---|--|--|--|
| KL | Rotary Panel 0/1-10V Dimmer |  | Input voltage:AC100-240V Output signal:0/1-10V (50mA) Output current:Max 3A (AC OUT) Input signal:Rotary knob, RF 2.4GHz Control distance:30m(Barrier-free space) Product size:86x86x48.5mm(LxWxH) | <ul style="list-style-type: none"> ● Output 1 channel 0/1-10V signal, high voltage AC relay output. ● 0-10V or 1-10V output selectable by DIP switch. ● Rotate knob to change brightness, support push and long push operation. ● Match with RF 2.4G single zone or multiple zone remote control optional. | 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A RF Remote Control:R11, RT1, RT6 | / |
| T18-2 | Rotary Glass Panel 0/1-10V Dimmer |  | Input voltage:AC100-240V Output signal:0/1-10V (50mA) Output current:Max 3A (AC OUT) Input signal:Rotary knob, RF 2.4GHz Control distance:10m(Barrier-free space) Product size:86x86x48mm(LxWxH) | <ul style="list-style-type: none"> ● Output 1 channel 0/1-10V signal, high voltage AC relay output. ● 0-10V or 1-10V output selectable by DIP switch. ● Rotate knob to change brightness, support push and long push operation. ● Match with RF 2.4G single zone or multiple zone remote control optional. | 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A RF Remote Control:R11, RT1, RT6 | / |
| T18 | Touch Glass Panel 0/1-10V Dimmer |  | Input voltage:AC100-240V Output signal:0/1-10V (50mA) Output current:Max 3A (AC OUT) Input signal:Touch key, RF 2.4GHz Control distance:10m(Barrier-free space) Product size:86x86x33mm(LxWxH) | <ul style="list-style-type: none"> ● Output 1 channel 0/1-10V signal,High voltage AC relay output. ● 0-10V or 1-10V output selectable by DIP switch. ● Supports 20 seconds delayed light off. ● Supports dynamic fade effect, speed adjustable. ● Match with RF 2.4G single zone or multiple zone remote control optional. | 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage Driver:LPV-150M-24 0-10V Constant Current Driver:LF-12A, LF-20A RF Remote Control:R11, RT1, RT6 | T18, T18-1 Contrast: Difference: 1. Number of output signal channels is different; T18 output single channel 0/1-10V signal, T18-1 output 4 channel 0/1-10V signal. 2. Output signal, current is different: T18 output current:0-10V (50mA), T18-1 output current:0-10V (20mA). 3. AC Relay Output: T18 has AC Relay Output, T18-1 has no AC Relay Output. |
| T18-1 | Touch Glass Panel 4 Channel 0-10V Dimmer |  | Input voltage:AC100-240V Output signal:4CH 0-10V (20mA/CH) Output current:20mA/CH Input signal:Touch key, RF 2.4GHz Control distance:10m(Barrier-free space) Product size:86x86x33mm(LxWxH) | <ul style="list-style-type: none"> ● 4 channel 0-10V output signal, 4 zone control. ● 3 scene memory. ● Match with 4-zone dimming RF remote control optional. | 0-10V Constant Voltage LED Controller:LV, LV-L, L4-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A 4-Zone RF Remote Control:RT6, RS1 | |
| T2-L | Touch Glass Panel 2-Channel Color Temperature 0/1-10V Dimmer |  | Input voltage:AC100-240V Output signal:2CH 0/1-10V Output current:20mA/CH Input signal:Touch key, RF 2.4GHz Control distance:10m(Barrier-free space) Product size:86x86x33mm(LxWxH) | <ul style="list-style-type: none"> ● 2 channel 0-10V output signal for CCT dimming. ● The two channel output can be set as warm white and cool white respectively, or one for brightness adjust and the other for color temperature adjust. ● 0-10V or 1-10V output selectable by DIP switch. ● 4 scene memory. ● Compatibility with RF 2.4G single zone or multiple zone color temperature remote control. | 0-10V Constant Voltage LED Controller:LV2, L4-L 0-10V CCT Constant Current LED Driver:LF-12A-2, LF-20A-2 Color Temperature Remote Control:R12, RT2, RT7 | / |


RF 0/1-10V Dimmer

| Model Name | Product Name | Pictrue | Parameters | Key Feature | Recommended Products | Distinguish Between Similar Products |
|------------|-----------------------------|---|---|---|---|--------------------------------------|
| L1 | RF 0/1-10V Dimmer |  | Input voltage:AC100-240V Input signal:RF 2.4GHz, AC Push Switch Output signal:0-10V (20mA) Control distance:30m(Barrier-free space) Product size:52x52x26mm(LxWxH) | <ul style="list-style-type: none"> ● Output 1 channel 0/1-10V signal. ● 0-10V or 1-10V output selectable by DIP switch. ● Compatibility with RF 2.4G single zone or multiple zone dimming remote control. ● Connect with external push switch to achieve on/off and dimming function. | 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A RF Remote Control:R11, RT1, RT6 | / |
| L1 (WT) | WiFi+RF 0/1-10V Dimmer |  | Input voltage:AC100-240V Input signal:WiFi, RF 2.4GHz, AC Push Switch Output signal:0/1-10V (20mA) Control distance:30m(Barrier-free space) Product size:52x52x26mm(LxWxH) | <ul style="list-style-type: none"> ● Output 1 channel 0/1-10V signal. ● Tuya APP cloud control, support on/off, brightness adjust, delay turn on/off light, timer run, scene function. ● Voice control, support for Amazon Alexa, Google Assistant, Tmall Genie and Xiaodu smart speakers. ● 0-10V or 1-10V output selectable by DIP switch. ● Compatibility with RF 2.4G single zone or multiple zone dimming remote control. ● Connect with external push switch to achieve on/off and dimming function. | 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A RF Remote Control:R11, RT1, RT6 | / |
| L1 (WZ) | Zigbee+RF 0/1-10V Dimmer |  | Input voltage:AC100-240V Input signal:Zigbee 3.0, RF 2.4GHz, AC Push Switch Output signal:0/1-10V (20mA) Control distance:30m(Barrier-free space) Product size:52x52x26mm(LxWxH) | <ul style="list-style-type: none"> ● Output 1 channel 0/1-10V signal. ● Tuya APP cloud control, support on/off, brightness adjust, delay turn on/off light, timer run, scene function. ● Philips HUE APP control by connect with Philips HUE bridge. ● Voice control, support for Amazon Alexa, Google Assistant, Tmall Genie and Xiaodu smart speakers. ● 0-10V or 1-10V output selectable by DIP switch. ● Compatibility with RF 2.4G single zone or multiple zone dimming remote control. ● Connect with external push switch to achieve on/off and dimming function. | 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A Zigbee Gateway:WG-Z RF Remote Control:R11, RT1, RT6 | / |



| | | | | | | |
|--------|--|---|--|--|--|---|
| L1(WB) | Bluetooth+RF 0/1-10V Dimmer |  | Input voltage:AC100-240V Input signal:Bluetooth,RF 2.4GHz, AC Push Switch Output signal:0/1-10V(20mA) Control distance:30m(Barrier-free space) Product size:52x52x26mm(LxWxH) | <ul style="list-style-type: none"> ● Output 1 channel 0/1-10V signal. ● Tuya APP cloud control, support on/off, brightness adjust, delay turn on/off light, timer run, scene function. ● Voice control, support for Amazon Alexa, Google Assistant, Tmall Genie and Xiaodu smart speakers. ● 0-10V or 1-10V output selectable by DIP switch. ● Compatibility with RF 2.4G single zone or multiple zone dimming remote control. ● Connect with external push switch to achieve on/off and dimming function. | 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A Bluetooth Gateway:WG-B RF Remote Control:R11, RT1, RT6 | / |
| L2 | RF 2 Channel 0/1-10V Dimmer |  | Input voltage:AC100-240V Input signal:RF 2.4GHz, AC Push Switch Output signal:2x0/1-10V Output current:0/1-10V: 50mA/CH AC: Max 3A Control distance:30m(Barrier-free space) Product size:175x45x27mm(LxWxH) | <ul style="list-style-type: none"> ● Output 2 channel 0/1-10V signal. ● 0-10V or 1-10V output selectable by DIP switch. ● Dimming or dual color control selectable by DIP switch. ● For dual color control, the two channel output can be set as warm white and cool white respectively, or one for brightness adjust and the other for color temperature adjust. ● Compatibility with RF 2.4G single zone or multiple zone dimming or color temperature remote control. ● Connect with external push switch to achieve on/off and dimming function. | 0-10V Constant Voltage LED Controller:LV2, L4-L 0-10V CCT Constant Current LED Driver:LF-12A-2, LF-20A-2 Color Temperature RF remote Control:R12, RT2, RT7 | / |
| L2(WT) | WiFi+RF 2 Channel 0/1-10V Dimmer |  | Input voltage:AC100-240V Input signal:WiFi, RF 2.4GHz, AC Push Switch Output signal:2x0/1-10V Output current:0/1-10V: 50mA/CH AC: Max 3A Control distance:30m(Barrier-free space) Product size:175x45x27mm(LxWxH) | <ul style="list-style-type: none"> ● Output 2 channel 0/1-10V signal. ● Tuya APP cloud control, support on/off, brightness adjust, delay turn on/off light, timer run, scene function. ● Voice control, support for Amazon Alexa, Google Assistant, Tmall Genie and Xiaodu smart speakers. ● 0-10V or 1-10V output selectable by DIP switch. ● Dimming or dual color control selectable by DIP switch. ● For dual color control, the two channel output can be set as warm white and cool white respectively, or one for brightness adjust and the other for color temperature adjust. ● Compatibility with RF 2.4G single zone or multiple zone dimming or color temperature remote control. ● Connect with external push switch to achieve on/off and dimming function. | 0-10V Constant Voltage LED Controller:LV2, L4-L 0-10V CCT Constant Current LED Driver:LF-12A-2, LF-20A-2 Color Temperature RF remote Control:R12, RT2, RT7 | / |
| L2(WZ) | Zigbee+RF 2 Channel 0/1-10V Dimmer |  | Input voltage:AC100-240V Input signal:Zigbee 3.0, RF 2.4GHz, AC Push Switch Output signal:2x0/1-10V Output current:0/1-10V: 50mA/CH AC: Max 3A Control distance:30m(Barrier-free space) Product size:175x45x27mm(LxWxH) | <ul style="list-style-type: none"> ● Output 2 channel 0/1-10V signal. ● Tuya APP cloud control, support on/off, brightness adjust, delay turn on/off light, timer run, scene function. ● Philips HUE APP control by connect with Philips HUE bridge. ● Voice control, support for Amazon Alexa, Google Assistant, Tmall Genie and Xiaodu smart speakers. ● 0-10V or 1-10V output selectable by DIP switch. ● Dimming or dual color control selectable by DIP switch. ● For dual color control, the two channel output can be set as warm white and cool white respectively, or one for brightness adjust and the other for color temperature adjust. ● Compatibility with RF 2.4G single zone or multiple zone dimming or color temperature remote control. ● Connect with external push switch to achieve on/off and dimming function. | 0-10V Constant Voltage LED Controller:LV2, L4-L 0-10V CCT Constant Current LED Driver:LF-12A-2, LF-20A-2 Zigbee Gateway:WG-Z Color Temperature RF remote Control:R12, RT2, RT7 | / |
| L4-M | RF 4 Channel 0/1-10V Dimmer |  | Input voltage:AC100-240V or 12VDC Output signal:4 x 0-10V Output current:4CH, 10mA/CH Product size:114x38x20mm(LxWxH) | <ul style="list-style-type: none"> ● Output 4 channel 0-10V signal. ● Match with RF 2.4G single color, dual color and RGB/RGBW remote control. | 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A RF Remote Control:R11, RT1, RT6 | / |

DMX 0/1-10V signal converter

| Model Name | Product Name | Pictrue | Parameters | Key Feature | Recommended Products | Distinguish Between Similar Products |
|------------|--------------------------------------|---|---|--|--|--------------------------------------|
| DL-L | 4 Channels 0/1-10V DMX512 Decoder |  | Input voltage:12-24VDC or 100-240VAC Input signal:DMX512 Output signal:0/1-10V, 4CH, 20mA/CH Product size:170x50x23mm(LxWxH) | <ul style="list-style-type: none"> ● Digital numeric display, set DMX decode start address by buttons. ● 1/2/4 DMX channel output selectable. ● Supports RDM function. ● 0-10V or 1-10V output selectable. ● Logarithmic or linear dimming curve selectable. ● Stand-alone RGB/RGBW mode and 4 channel dimmer mode selectable. ● Built-in 24 RGB change modes with adjustable speed and brightness. | DMX512 Console:Channel dimming, dynamic effects edit. DMX Master Control Panel:T11-S, T11-1, T11-K WiFi APP Control:WT-DMX-S Zigbee Control:WZ-DMX-S 0-10V Constant Voltage LED Controller:LV, LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A, LF-20A | / |

| | | | | | | |
|----|-----------------------------------|---|--|--|--|---|
| DL | 4 Channels 0/1-10V DMX512 Decoder |  | <p>Input voltage:12-24VDC Input signal:DMX512 Output signal:0/1-10V, 4CH, 20mA/CH Product size:110x48x67mm(LxWxH)</p> | <ul style="list-style-type: none"> ● Digital numeric display, set DMX decode start address by buttons. ● 1/2/4 DMX channel output selectable. ● Supports RDM function. ● 0-10V or 1-10V output selectable. ● Logarithmic or linear dimming curve selectable. ● Stand-alone RGB/RGBW mode and 4 channel dimmer mode selectable. ● Built-in 24 RGB change modes with adjustable speed and brightness. ● Standard rail mount. | <p>DMX512 Console:Channel dimming,dynamic effects edit. DMX Master Control Panel:T11-S,T11-1,T11-K WiFi APP Control:WT-DMX-S Zigbee Control:WZ-DMX-S</p> <p>0-10V Constant Voltage LED Controller: LV,LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LED:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A,LF-20A</p> | / |
|----|-----------------------------------|---|--|--|--|---|

DALI 0/1-10V Dimmer

| Model Name | Product Name | Pictrue | Parameters | Key Feature | Recommended Products | Distinguish Between Similar Products |
|------------|---------------------|---|---|--|--|--------------------------------------|
| DV | DALI 0/1-10V Dimmer |  | <p>Input voltage:100-240VAC Input signal:DALI Output signal:2x(0/1-10)V, 20mA/CH Relay output:Max. 5A Product size:187x46x22mm(LxWxH)</p> | <ul style="list-style-type: none"> ● 2 DALI address, 2 channel 0/1-10V output. ● Digital display, two-button setting. ● DALI address can be manually assigned and shown in digital display or automatically assigned by DALI master. ● High voltage AC input, one high voltage AC relay output. ● 0-10V or 1-10V output selectable. | <p>DALI PC Host:Assignment of DALI address,dimming control DALI Master Control Panel:TD1-S,TD1-4S,TD-K,TS4-D WiFi APP Control:DA-M(WT),TD-K(WT) Zigbee Control:DA-M(WZ),TD-K(WZ)</p> <p>0-10V Constant Voltage LED Controller:LV,LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LED:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A,LF-20A</p> | / |
| DV1 | DALI 0/1-10V Dimmer |  | <p>Input voltage:100-240VAC Input signal:DALI Output signal:0/1-10V, 20mA Relay output:10A resistive load 5A incandescent 5A inductive load Product size:131x37x20.5mm(LxWxH)</p> | <ul style="list-style-type: none"> ● 1 DALI address, 1 channel 0/1-10V output. ● Assignment of DALI addresses by DALI master. ● 10A dry contact mains rated relay output. ● 0-10V or 1-10V output selectable. | <p>DALI PC Host:Assignment of DALI address,dimming control DALI Master Control Panel:TD1-S,TD1-4S,TD-K,TS4-D WiFi APP Control:DA-M(WT),TD-K(WT) Zigbee Control:DA-M(WZ),TD-K(WZ)</p> <p>0-10V Constant Voltage LED Controller:LV,LV-L 0-10V Constant Voltage Triac Dimmer:S1-L 0-10V Constant Voltage LED Driver:LED:LPV-150M-24 0-10V Constant Current LED Driver:LF-12A,LF-20A</p> | / |