

















RF Color Temperature Remote Control (Handheld)

Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
R12	1 Zone Color Temperature Remote Control		Working voltage:3VDC (CR2032) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m (Barrier-free space) Proudct size:139x36x11mm (LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature slide to adjust the color temperature, long press the on/off key to adjust the brightness. ● Red indicator is displayed during operation. ● Magnet on the back which can be easily stuck on back holder or any metal surfaces. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/
R7-1	1 Zone Color Temperature Remote Control		Working voltage:3VDC (CR2032) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m (Barrier-free space) Proudct size:107x58.5x9mm (LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature wheel to adjust the color temperature. ● 3 scene memory. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/
R7	4 Zone Color Temperature Remote Control		Working voltage:3VDC (CR2032) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m (Barrier-free space) Proudct size:107x58.5x9mm (LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature wheel to adjust the color temperature. ● 3 scene memory. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/
RT2	1 Zone Color Temperature Remote Control		Working voltage:3VDC (AAAx2) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m (Barrier-free space) Proudct size:122x53x17.5mm (LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature wheel to adjust the color temperature. ● 4 scene memory. ● Color indicator is displayed during operation. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/
RT7	4 Zone Color Temperature Remote Control		Working voltage:3VDC (AAAx2) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m (Barrier-free space) Proudct Size:122x53x17.5mm (LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature wheel to adjust the color temperature. ● 4 scene memory. ● Color indicator is displayed during operation. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/
RT8C	8 Zone Color Temperature Remote Control		Working voltage:3VDC (AAAx2) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m (Barrier-free space) Proudct size:122x53x17.5mm (LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature wheel to adjust the color temperature. ● 2 scene memory. ● Color indicator is displayed during operation. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/
R2	1 Zone Color Temperature Remote Control		Working voltage:3VDC (AAAx2) Working current:<5mA Standby current:<2uA Standby time:2 year Output signal:RF 2.4GHz Remote distance:30m (Barrier-free space) Proudct size:135x40x11mm (LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● 2 scene memory. ● Red indicator is displayed during operation. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/
RM2	1 Zone Color Temperature Remote Control		Working voltage:3VDC (AAAx2) Working current:<5mA Standby current:<2uA Standby time:2 year Output signal:RF 2.4GHz Remote distance:30m (Barrier-free space) Proudct size:100x47x8mm (LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Delay light off key supports 30s/60s delay light off. ● Red indicator is displayed during operation. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/

RS2	4 Zone Color Temperature Remote Control		Working voltage:3VDC(AAAx2) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:155x43x17.5mm(LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature wheel to adjust the color temperature. ● 3 scene memory. ● Color indicator is displayed during operation. ● Magnet on the back which can be easily stuck on back holder or any metal surfaces. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/
RK4-2	1 Zone Color Temperature Remote Control		Working voltage:3VDC(CR2032) Working current:<5mA Standby current:<2uA Standby time:2 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:75x18mm(DxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Short press the color temperature key to switch 5 levels color temperature sequentially. ● Red indicator is displayed during operation. ● Magnet on the back which can be easily stuck on back holder or any metal surfaces. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF CCT Constant Voltage LED Panel Controller:T2-K, T2-1 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M, TD2-S	/

RF Color Temperature Panel Remote Control (Battery Powered)

Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
RK2	1 Zone Color Temperature Rotary Panel Remote Control (Desktop)		Working voltage:3VDC(CR2032) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:91x72x57mm(LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Short press knob switch, rotate knob adjust color temperature or brightness (double click to switch). ● Desk mount, removeable anywhere easily. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF 0/1-10V Dimmer:L2 (WT) RF-DALI Signal Converter:DA-M	/
PK2	1 Zone Color Temperature Rotary Panel Remote Control		Working voltage:3VDC(CR2032) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:86x86x23mm(LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Short press knob switch, rotate knob adjust color temperature or brightness (double click to switch). ● Red indicator is displayed during operation. ● Removeable and stick anywhere easily or mount on wall use panel base. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
PF2	1 Zone Color Temperature Keypad Remote Control		Working voltage:3VDC(CR2032) Working current:<5mA Standby current:<2uA Standby time:2 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:86x86x14mm(LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Red indicator is displayed during operation. ● Removeable and stick anywhere easily or mount on wall use panel base. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
TW2	1 Zone Color Temperature Touch Panel Remote Control		Working voltage:3VDC(CR2032) Working current:<8mA Standby current:<16uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:86x86x9.5mm(LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature wheel to adjust the color temperature. ● 4 scene memory. ● Red and blue indicator is displayed during operation. ● Stick anywhere or mount on wall use panel base. ● The back surface contains magnet that can be attached to the metal surface. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
TW2-4	4 Zone Color Temperature Touch Panel Remote Control		Working voltage:3VDC(CR2032) Working current:<8mA Standby current:<16uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:86x86x9.5mm(LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature wheel to adjust the color temperature. ● 2 scene memory. ● Red and blue indicator is displayed during operation. ● Stick anywhere or mount on wall use panel base. ● The back surface contains magnet that can be attached to the metal surface. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
T22	4 Zone Color Temperature Touch Panel Remote Control		Working voltage:3VDC(AAAx2) Working current:<5mA(Without tune) <20mA(with tune) Standby current:<20uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:86x86x20.5mm(LxWxH)	<ul style="list-style-type: none"> ● Apply to color temperature LED RF controller and RF dimming driver. ● Touch the color temperature slide to adjust the color temperature. ● 1 scene memory. ● Red and blue indicator is displayed during operation. ● Stick anywhere or mount on wall use panel base. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/

RF Color Temperature Panel Remote Control (AC100-240V Powered)

Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
T12-K	1 Zone Color Temperature Rotary Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Proudct size:86x86x48mm(LxWxH)	<ul style="list-style-type: none"> ● Can be used as either a single zone color temperature DMX512 master or a single zone color temperature RF remote control. ● Short press knob switch, rotate knob adjust color temperature or brightness (double click to switch). ● Blue indicator is displayed during operation. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
T12-S	1 Zone Color Temperature Touch Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Proudct size:86x86x33mm(LxWxH)	<ul style="list-style-type: none"> ● Can be used as either a single zone color temperature DMX512 master or a single zone color temperature RF remote control. ● Touch the color temperature slide to adjust the color temperature, touch the brightness slide to adjust 1-100% brightness. ● 4 scene memory. ● Blue indicator is displayed during operation. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
T12-4S	4 Zone Color Temperature Touch Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Proudct size:86x86x33mm(LxWxH)	<ul style="list-style-type: none"> ● Can be used as either a 4 zone color temperature DMX512 master or a 4 zone color temperature RF remote control. ● Touch the color temperature slide to adjust the color temperature, touch the brightness slide to adjust 1-100% brightness. ● 3 scene memory. ● Blue indicator is displayed during operation. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
T12	4 Zone Color Temperature Touch Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Proudct size:86x86x33mm(LxWxH)	<ul style="list-style-type: none"> ● Can be used as either a 4 zone color temperature DMX512 master or a 4 zone color temperature RF remote control. ● Touch the color temperature wheel to adjust the color temperature. ● 4 scene memory. ● Red and blue indicator is displayed during operation. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
T12-1	4 Zone Color Temperature Touch Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Proudct size:86x86x33mm(LxWxH)	<ul style="list-style-type: none"> ● Can be used as either a 4 zone color temperature DMX512 master or a 4 zone color temperature RF remote control. ● Touch the color temperature slide to adjust the color temperature. ● 1 scene memory. ● Red and blue indicator is displayed during operation. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/
T12(IT)	4 Zone Color Temperature Touch Panel Remote Control (Italian Standard)		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Proudct size:120x80x37mm(LxWxH)	<ul style="list-style-type: none"> ● Can be used as either a 4 zone color temperature DMX512 master control or a 4 zone color temperature RF remote control. ● Touch the color temperature ring to adjust the color temperature. ● Red and blue indicator is displayed during operation. ● White & Black available. 	RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2	/