




**RF RGB+CCT Remote Control (Handheld)**






Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
R10	1 Zone RGB+CCT Remote Control		Working voltage:3VDC (CR2032) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Proudct size:139x36x11mm (LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT LED RF controller.</li> <li>● Touch the color slide to adjust the color or color temperature, long press the on/off key to adjust the brightness.</li> <li>● Double-click the on/off key to switch between RGB or CCT mode.</li> <li>● Red indicator is displayed during operation.</li> <li>● Magnet on the back which can be easily stuck on back holder or any metal surfaces.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/
R17	1 Zone RGB+CCT Remote Control		Working voltage:3VDC (CR2032) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Proudct size:107x58.5x9mm (LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT LED RF controller.</li> <li>● Touch the color wheel to adjust the color or color temperature.</li> <li>● R/G/B channel independent dimming for millions of colors.</li> <li>● 1 scene memory.</li> <li>● Red indicator is displayed during operation.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/
R8-5	4 Zone RGB+CCT Remote Control		Working voltage:3VDC (CR2032) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Proudct size:107x58.5x9mm (LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT, RGBW, RGB, CCT LED RF controller.</li> <li>● Compatible with multiple light type control, each zone can be set to dimming, color temperature, RGB, RGBW or RGB+CCT light type separately.</li> <li>● Touch the color wheel to adjust the color or color temperature.</li> <li>● Red indicator is displayed during operation.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5 RF RGBW Constant Voltage LED Controller:VP, V4, V4-S, V4-X, V4-M, V4-WPS RF RGB Constant Voltage LED Controller:V3, V3-L, V3-C, V3-M, V3-W, VD3 RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF Dimming Constant Voltage LED Controller:V1, V1-L, V1-C, V1-M, V1-W, VD1	/
RT5	1 Zone RGB+CCT Remote Control		Working voltage:3VDC (AAAx2) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Proudct size:122x53x17.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT LED RF controller.</li> <li>● Touch the color wheel to adjust the color or color temperature.</li> <li>● R/G/B channel independent dimming for millions of colors.</li> <li>● 2 scene memory.</li> <li>● Color indicator is displayed during operation.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/
RT10	4 Zone RGB+CCT Remote Control		Working voltage:3VDC (AAAx2) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Proudct size:122x53x17.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT, RGBW, RGB, CCT LED RF controller.</li> <li>● Compatible with multiple light type control, each zone can be set to dimming, color temperature, RGB, RGBW or RGB+CCT light type separately.</li> <li>● Touch the color wheel to adjust the color or color temperature.</li> <li>● 2 scene memory.</li> <li>● Color indicator is displayed during operation.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5 RF RGBW Constant Voltage LED Controller:VP, V4, V4-S, V4-X, V4-M, V4-WPS RF RGB Constant Voltage LED Controller:V3, V3-L, V3-C, V3-M, V3-W, VD3 RF CCT Constant Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF Dimming Constant Voltage LED Controller:V1, V1-L, V1-C, V1-M, V1-W, VD1	/
RS10	8 Zone 8 Sence Remote Control		Working voltage:3VDC (AAAx2) Working current:<5mA Standby current:<10uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Proudct size:141x50x17.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT, RGBW, RGB, CCT LED RF controller.</li> <li>● Compatible with multiple light type control, each zone can be set to dimming, color temperature, RGB, RGBW or RGB+CCT light type separately.</li> <li>● Touch the color wheel to adjust the color or color temperature.</li> <li>● 8 scene memory.</li> <li>● Color indicator is displayed during operation.</li> <li>● Magnet on the back which can be easily stuck on back holder or any metal surfaces.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5 RF RGBW Constant Voltage LED Controller:VP, V4, V4-S, V4-X, V4-M, V4-WPS RF RGB Constant Voltage LED Controller:V3, V3-L, V3-C, V3-M, V3-W, VD3 RF CCT Voltage LED Controller:V2, V2-L, V2-C, V2-M, V2-W, VD2 RF Dimming Constant Voltage LED Controller:V1, V1-L, V1-C, V1-M, V1-W, VD1	/

**RF RGB+CCT Panel Remote Control (Battery Powered)**

Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
TW5	1 Zone RGB+CCT Touch Panel Remote Control		Working voltage:3VDC (CR2032) Working current:<8mA Standby current:<16uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Proudct size:86x86x9.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT LED RF controller.</li> <li>● Touch the color wheel to adjust color.</li> <li>● 2 scene memory.</li> <li>● Red and blue indicator is displayed during operation.</li> <li>● Stick anywhere or mount on wall use panel base.</li> <li>● The back contains magnet that can be attached to the metal surface.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/

TW5-4	4 Zone RGB+CCT Touch Panel Remote Control		Working voltage:3VDC (CR2032) Working current:<8mA Standby current:<16uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:86x86x9.5mm(LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT LED RF controller.</li> <li>● Touch the color wheel to adjust color.</li> <li>● Red and blue indicator is displayed during operation.</li> <li>● Stick anywhere or mount on wall use panel base.</li> <li>● The back contains magnet that can be attached to the metal surface.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/
T25	4 Zone RGB+CCT Touch Panel Remote Control		Working voltage:3VDC (AAx2) Working current:<5mA (without tune) <20mA (with tune) Standby current:<20uA Standby time:1 year Output signal:RF 2.4GHz Remote distance:30m(Barrier-free space) Product size:86x86x20.5mm(LxWxH)	<ul style="list-style-type: none"> <li>● Apply to RGB+CCT LED RF controller.</li> <li>● Touch the color slide to adjust the color or color temperature.</li> <li>● Red and blue indicator is displayed during operation.</li> <li>● Stick anywhere or mount on wall use panel base.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/

**RF RGB+CCT Panel Remote Control (AC100-240V Powered)**

Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
T15-S	1 Zone RGB+CCT Touch Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Product size:86x86x33mm(LxWxH)	<ul style="list-style-type: none"> <li>● Can be used as either a single zone RGB+CCT DMX512 master or a single zone RGB+CCT RF remote control.</li> <li>● 4 scene memory.</li> <li>● Supports a variety of jump or fade dynamic effects.</li> <li>● Blue indicator is displayed during operation.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/
T15-4S	4 Zone RGB+CCT Touch Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Product size:86x86x33mm(LxWxH)	<ul style="list-style-type: none"> <li>● Can be used as either a 4 zone RGB+CCT DMX512 master or a 4 zone RGB+CCT RF remote control.</li> <li>● 3 scene memory.</li> <li>● Supports a variety of jump or fade dynamic effects.</li> <li>● Blue indicator is displayed during operation.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/
T15	4 Zone RGB+CCT Touch Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Product size:86x86x33mm(LxWxH)	<ul style="list-style-type: none"> <li>● Can be used as either a 4 zone RGB+CCT DMX512 master or a 4 zone RGB+CCT RF remote control.</li> <li>● Touch the color wheel to adjust color.</li> <li>● 3 scene memory.</li> <li>● Supports a variety of jump or fade dynamic effects.</li> <li>● Red and blue indicator is displayed during operation.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/
T15-1	4 Zone RGB+CCT Touch Panel Remote Control		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Product size:86x86x33mm(LxWxH)	<ul style="list-style-type: none"> <li>● Can be used as either a 4 zone RGB+CCT DMX512 master or a 4 zone RGB+CCT RF remote control.</li> <li>● Touch the color slide to adjust the color or color temperature.</li> <li>● Supports a variety of jump or fade dynamic effects.</li> <li>● Red and blue indicator is displayed during operation.</li> <li>● White &amp; Black available.</li> </ul>	RF RGB+CCT Constant Voltage LED Controller:V5-M, V5, V5-L, WT5	/
T15(IT)	4 Zone RGB+CCT Touch Panel Remote Control (Italian Standard)		Input voltage:AC100-240V Output signal:DMX512, RF 2.4GHz Remote distance:10m(Barrier-free space) Product size:120x80x37mm(LxWxH)	<ul style="list-style-type: none"> <li>● Can be used as either a 4 zone RGB+CCT DMX512 master or a 4 zone RGB+CCT RF remote control.</li> <li>● Touch the color wheel to adjust the color or color temperature.</li> <li>● 1 scene memory.</li> <li>● Supports a variety of jump or fade dynamic effects.</li> <li>● Red and blue indicator is displayed during operation.</li> <li>● White &amp; Black available.</li> </ul>		/